



4500



## Features

- Efficient glue wheel transfer to minimize glue consumption
- PLC controlled for reliability and ease of operation
- Quick change components reduces changeover time
- Fewer moving parts reduces maintenance cost
- Small footprint takes up minimal space
- Industry's strongest field service organization reduces downtime
- Accraply quality and performance you expect

# Trine 4500 Roll-Fed Labelling System


## Smaller Size, Same Quality...

The 4500 roll fed wraparound system has been designed with a 30% smaller footprint and provides labeling speeds up to 350 cpm. Equipped with quick change parts, a product changeover can take one person less than 20 minutes with just a single tool guaranteed. To provide precise label application the 4500 is designed with the latest in glue application technology and label registration control. With advanced technology, quicker changeovers, and affordable change parts, the 4500 provides a roll fed labeling system ideal for any demanding environment.

With applications in beverage, food, pharmaceutical, cosmetic, dairy, aerosol and nutritional product industries, Trine roll fed labeling systems have proven their versatility. Trine roll fed labelers provide ongoing savings by replacing higher-cost cut labels. Additionally, Trine systems can even be used to label contour containers with Trine's patented Roll 'n' Shrink technology.

## Options

- Infeed screw drive
- Discharge stabilizer assembly
- Clear label sensor and low label detection
- Air conditioned electrical enclosure
- Servo-driven label registration system
- CE-Certified upgrade
- Alternative voltages, conveyor heights, and colors
- Custom product handling



Maximum Speed:	350 Containers per Minute
Repeat Length:	6.5" to 16.5" [1.53.4mm to 419.1mm]
Web Width:	1" to 8.25" [25.4mm to 209.6mm]
Diameter:	1.75" to 5" [44.5mm to 127mm]
Air	80 psi (5.52 bar), 12-15 cfm (340-425 L/min)
Electrical:	240 VAC, 3-Phase, 50/60hz
Weight:	3700 lbs [1,678 kg]

*\* All specification and tooling requirements are subject to Accraply evaluation of all label and product samples. Specifications shown reflect standard machine capabilities. Accraply can also meet other specification requirements. Please call for details.*

Accraply

Trine

Stanford

Graham

Sleevit

Harland

## Accraply

3580 Holly Lane North  
Plymouth MN 55447-1269 USA

t. +1 (763) 557-1313  
[accraply.com](http://accraply.com)

